

5 - KIT STRIP 5mt

5.1 - KIT 5mt Strip LED 3.2x2.8



Applicazioni:

- Illuminazione decorativa
- Linee di luce
- Retroilluminazione



Applications:

- Decorative lighting
- Lines of light
- Backlight

Caratteristiche:

- Alimentazione **12VDC** versione 120LED/m e 240LED/m **24VDC**
- Strip LED flessibile biadesiva 3M e supporto in kapton UL
- Angolo di emissione 120°
- Identificazione della polarità
- Collegamenti tramite piazzole da saldare

Features:

- Supply **12VDC** version 120LED/m and 240LED/m **24VDC**
- Flexible LED Strip 3M UL double side adhesive kapton support
- Emission angle 120°
- Polarity identification
- Connections by welded spots

Note:

- Dimensioni: L x 9mm spessore 2.25mm
- Dimensioni 240LED/m: L x 10mm spessore 2.25mm
- Strip con adesivo **3M**
- Compatibile con i profili in alluminio/PVC
- Tc +60°C
- Ta -10 +25°C

Notes:

- Dimensions: L x 9mm thickness 2.25mm
- Dimensions 240LED/m: L x 10mm thickness 2.25mm
- Adhesive strip **3M**
- Compatible with the aluminum profile/PVC
- Tc +60°C
- Ta -10 +25°C

Codice acquisto Acquisition code	Codice interno Internal code	Modello LED LED model	Colore Colour	N° di LED	P @ Voltage	Φ @ (Lumen)	L (separabile ogni) (separable every)
05000	KIT30WKHNG	SMD 3.2x2.8	B.caldo/Warm white	30LED/m	2.4 W/m-12Vdc	87 lm/m	100 mm
05001	KIT60WKHNG	SMD 3.2x2.8	B.caldo/Warm white	60LED/m	4.8 W/m-12Vdc	174 lm/m	50 mm
05002	KIT120WKHNG	SMD 3.2x2.8	B.caldo/Warm white	120LED/m	9.6 W/m-24Vdc	348 lm/m	50 mm
05006	KIT240WKHNG	SMD 3.2x2.8	B.caldo/Warm white	240LED/m	19 W/m-24Vdc	1000 lm/m	25 mm
05004	KIT30WHNG	SMD 3.2x2.8	B.freddo/Cold white	30LED/m	2.4 W/m-12Vdc	111 lm/m	100 mm
05003	KIT60WHNG	SMD 3.2x2.8	B.freddo/Cold white	60LED/m	4.8 W/m-12Vdc	222 lm/m	50 mm
05005	KIT120WHNG	SMD 3.2x2.8	B.freddo/Cold white	120LED/m	9.6 W/m-24Vdc	444 lm/m	50 mm
05007	KIT240WHNG	SMD 3.2x2.8	B.freddo/Cold white	240LED/m	19 W/m-24Vdc	1200 lm/m	25 mm

5.2 - KIT 5mt Strip LED 5x5 High Brightness



Applicazioni:

- Illuminazione decorativa
- Linee di luce
- Retroilluminazione



Applications:

- Decorative lighting
- Lines of light
- Backlight

Caratteristiche:

- Alimentazione **12VDC** versione 60LED/m **24VDC**
- Strip LED flessibile biadesiva 3M e supporto in kapton UL
- Angolo di emissione 120°
- Identificazione della polarità
- Collegamenti tramite piazzole da saldare

Features:

- Supply **12VDC** version 60LED/m **24VDC**
- Flexible LED Strip 3M UL double side adhesive kapton support
- Emission angle 120°
- Polarity identification
- Connections by welded spots

Note:

- Dimensioni: L x 12mm spessore 2.25mm
- Strip con adesivo **3M**
- Compatibile con i profili in alluminio/PVC
- Tc +60°C
- Ta -10 +25°C

Notes:

- Dimensions: L x 12mm thickness 2.25mm
- Adhesive strip **3M**
- Compatible with the aluminum profile/PVC
- Tc +60°C
- Ta -10 +25°C

Codice acquisto Acquisition code	Codice interno Internal code	Modello LED LED model	Colore Colour	N° di LED	P @ Voltage	Φ @ (Lumen)	L (separabile ogni) (separable every)
05010	KIT530WKHNG	SMD 5x5	B.caldo/Warm white	30LED/m	7.2 W/m-12Vdc	480 lm/m	100 mm
05011	KIT560WKHNG	SMD 5x5	B.caldo/Warm white	60LED/m	14.4 W/m-24Vdc	960 lm/m	100 mm
05014	KIT530WKFHNG	SMD 5x5	B.neutro/Neutral white	30LED/m	7.2 W/m-12Vdc	520 lm/m	100 mm
05015	KIT560WKFHNG	SMD 5x5	B.neutro/Neutral white	60LED/m	14.4 W/m-24Vdc	1040 lm/m	100 mm
05012	KIT530WHNG	SMD 5x5	B.freddo/Cold white	30LED/m	7.2 W/m-12Vdc	540 lm/m	100 mm
05013	KIT560WHNG	SMD 5x5	B.freddo/Cold white	60LED/m	14.4 W/m-24Vdc	1080 lm/m	100 mm